



PRECISION COATINGS, INC.

---

## P R O D U C T     D A T A

---

### *12030* *Urethane Accelerator*

#### **DESCRIPTION:**

12030 Urethane Accelerator is a catalyst designed to accelerate the drying and cure times of PC3v100, PC3, and PC4 Topcoats and Clear Coats. This additive maintains excellent pot life stability while producing fast tack free and curing times.

#### **TECHNICAL DATA:**

PACKAGED VOC	107 g/l, 0.89 lbs/gal
PACKAGED VOC (less water & exempt compounds)	979g/l, 8.16 lbs/gal
SHELF LIFE	one year (unopened)
FLASH POINT	-4° F, -20° C
RECOMMENDED USE LEVEL	8 fluid ounces per gallon of activated Topcoat or Clear Coat

**DIRECTIONS FOR USE:** add up to 8 fluid ounces of 12030 Urethane Accelerator per activated gallon of Topcoat or Clear Coat.

*DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Precision Coatings, Inc. experience and research and is believed to be reliable. As PCI has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.*

PRECISION COATINGS, INC. • 1940 E. TRAFFICWAY, SPRINGFIELD, MO 65802  
PHONE (888) 340-6780 • FAX (888) 340-6783  
EMAIL: [precisioncoatingsinc.com](mailto:precisioncoatingsinc.com)