

MATERIAL SAFETY DATA SHEET

Product: Fisheye Eliminator; 15000
 Manufacturer's Name: Precision Coatings, Inc.
 Address: 1940 E. Trafficway, Springfield, Missouri, 65802

MSDS No. 15000
 Date Prepared: January 3, 2006
 Emergency Telephone
 Number: 800-424-9300 Chemtrec
 Other Information
 Calls: (417) 862-5738

SECTION-1 IDENTITY

Common Name (Used on Label): Fisheye Eliminator; 15000
 Chemical Name: Mixture
 Chemical Family: Ketone

CAS No: None
 Formula: 15000

SECTION-2 HAZARDOUS INGREDIENTS/IDENTITY

Hazardous Components	CAS No.	Vapor Pressure	ACGIH TLV TWA STEL	OSHA		
				PEL	CEILING	PEAK
Methyl n-amyl ketone	110-43-0	2.1mmHg	50ppm NE	100ppm	NE	NE

SECTION-3 PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point: 304° F, 152° C Specific Gravity: 0.81 Vapor Pressure (mm Hg): 2.1
 Percent Volatile by Volume: 100 Vapor Density (Air =1): 3.0 Evaporation Rate (Ether=1): Slower
 Solubility in Water: slight Reactivity in Water: None Appearance: colorless liquid
 Odor: pungent, sweet

VOC: 809 grams/liter, (6.75 lbs/gal)

SECTION-4 FIRE & EXPLOSION DATA

Flash Point: 102° F 39° C Method Used: Tag Closed Cup Auto-Ignition Temperature: 740° F 393° C
 Flammability Classification: OSHA: Combustible Liquid DOT: Combustible Liquid
 Extinguisher Media: NFPA Class B (CO₂, Dry Chemical, Foam)
 Flammable Limits in Air % by volume: LEL Lower: NE UEL Upper: NE
 Special Fire Fighting Procedures: Water spray may be ineffective on fire but can protect fire fighters and cool containers to prevent pressure buildup. Use fog nozzles if water is used. Full protective equipment, including self-contained breathing apparatus, is recommended.
 Unusual Fire and Explosion Hazards: When heated above the flash point, emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point. Closed containers may explode if exposed to extreme heat.

SECTION-5 PHYSICAL HAZARDS (REACTIVITY DATA)

Stability: Stable
 Conditions to Avoid: Keep away from heat, sparks, electrical equipment and open flame.
 Incompatibility (materials to avoid): Material can react violently with strong oxidizing agents
 Hazardous Decomposition Products: carbon dioxide, carbon monoxide.
 Hazardous Polymerization: Will not occur.

SECTION-6 HEALTH HAZARDS**Acute Overexposure:**

Skin: Prolonged or repeated contact may cause drying, cracking, or irritation.

Eye: High vapor concentrations may cause irritation.

Inhalation: High vapor concentrations may cause drowsiness and irritation.

Ingestion: Expected to be a low ingestion hazard.

Acute Toxicity Data:

Oral LD-50 (rat): 1600 mg/kg

Oral LD-50 (mouse): 730 mg/kg
Inhalation LC-50 (rat): 2000-4000 ppm/4 hours
Dermal LD-50 (rabbit): 12.6 mL/kg
Dermal LD-50 (guinea pig): >20 mL/kg
Skin irritation (rabbit): slight to moderate
Skin sensitization (human): none
Eye irritation (rabbit): slight

Notice: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Definitions for the following sections: LOEL-lowest observed effect level; NOAEL-no observed adverse effect level; NOEL-no observed effect level.

Subchronic Toxicity Data:

Oral study (13 weeks, rat): LOEL-100mg/kg (minor target organ effects: kidney) (increase in weight: liver); NOEL-20mg/kg/day.

Oral study (12 weeks, rat): NOEL-0.5% in drinking water (highest concentration tested)

Inhalation study (9 months, rat): NOEL-1025 ppm (highest concentration tested)

Inhalation study (9 months, monkey): NOEL-1025 ppm (highest concentration tested)

Carcinogenicity: None.

SECTION-7 FIRST AID

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Consult a physician.

Eye Contact: Flush with water for at least 15 minutes. Consult a physician.

Skin Contact: Wash with soap and water. If irritation persists, consult a physician.

Ingestion: DO NOT induce vomiting. Call a physician immediately. Have the names of ingredients available.

SECTION-8 SPECIAL PRECAUTIONS

Observe label precautions. Keep away from heat, sparks and flame. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120 degrees F. Do not flame cut, saw, braze or weld containers. Empty containers may contain hazardous product vapors.

SECTION-9 SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Remove all sources of ignition. Isolate from oxidizers. Ventilate area. Remove with inert materials and non-sparking tools.

Waste disposal methods: Dispose in accordance with all Federal, State and Local regulations. When discarded, this material is a hazardous waste.

SECTION-10 SPECIAL PROTECTION INFORMATION/CONTROL MEASURES

Do not breathe vapors or mists. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during application and handling unless air monitoring demonstrates vapor/mist levels below applicable limits. Follow respirator manufacturer's recommendations for selection and use.

Ventilation: Provide sufficient ventilation to keep vapor concentration below the given TLV and/or PEL.

Protective clothing: Solvent resistant gloves are required for prolonged or repeated contact. Refer to safety equipment supplier for effective glove recommendations.

Use safety goggles or safety glasses with splash guards or side shields to protect against splash of liquids.

Other protective equipment such as eye bath should be available. Use chemical resistant apron, boots or other clothing if needed to avoid repeated or frequent contact.

SECTION-11 REGULATORY INFORMATION

OSHA: This product is considered hazardous under the Federal OSHA Hazard Communication Standard.

SARA Title III Section 302 Extremely Hazardous Substances: None

SARA Title III Section 311/312 Hazard Categories: Immediate health, delayed health, fire hazard.

Section 313 Supplier Notification: The chemicals listed below with percentages are subject to the reporting requirements of Section 313 of the Emergency Planning and Right-To-Know Act of 1986 and of 40 CFR 372:

<u>CAS Number</u>	<u>Chemical Name</u>	<u>% by Weight</u>
NA	None	NA

Hazardous Air Pollutants: None

Hazardous Waste: When discarded in its supplied form, this product meets the hazard criteria of "ignitability" and must be considered as hazardous waste.

TSCA status: All ingredients are TSCA registered.

CEPA status: All ingredients are listed on the DSL or NDSL.

Proposition 65 Warning: This product does not contain chemicals known to the State of California to cause cancer or birth defects or other reproductive harm.

DOT Proper Shipping Name: Non-bulk shipments of this product are not regulated by DOT.

SECTION-12 OTHER INFORMATION

While Precision Coatings, Inc. believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Precision Coatings, Inc. assumes legal responsibility. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.